

## Features :


- Universal AC input / Full range
- Built-in active PFC function, PF>0.95
- High efficiency up to 90%
- **Optional L-Bracket and cover (ELP-75-x-C, x=3.3,5,12,15,24,36,48)**
- Protections: Short circuit / Overload / Over voltage
- Cooling by free air convection
- 1U low profile
- LED indicator for power on
- No load power consumption<0.5W
- 3 years warranty



## SPECIFICATION

| MODEL                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | ELP-75-3.3                                                                                                              | ELP-75-5    | ELP-75-12    | ELP-75-15      | ELP-75-24    | ELP-75-36    | ELP-75-48    |
|-----------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|-------------|--------------|----------------|--------------|--------------|--------------|
| OUTPUT                                  | DC VOLTAGE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 3.3V                                                                                                                    | 5V          | 12V          | 15V            | 24V          | 36V          | 48V          |
|                                         | RATED CURRENT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 15A                                                                                                                     | 15A         | 6.25A        | 5A             | 3.15A        | 2.1A         | 1.6A         |
|                                         | CURRENT RANGE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 0 ~ 15A                                                                                                                 | 0 ~ 15A     | 0 ~ 6.25A    | 0 ~ 5A         | 0 ~ 3.15A    | 0 ~ 2.1A     | 0 ~ 1.6A     |
|                                         | RATED POWER                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 49.5W                                                                                                                   | 75W         | 75W          | 75W            | 75.6W        | 75.6W        | 76.8W        |
|                                         | RIPPLE & NOISE (max.) <small>Note.2</small>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 80mVp-p                                                                                                                 | 80mVp-p     | 120mVp-p     | 150mVp-p       | 240mVp-p     | 280mVp-p     | 300mVp-p     |
|                                         | VOLTAGE ADJ. RANGE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 3 ~ 3.6V                                                                                                                | 4.75 ~ 5.5V | 10.8 ~ 13.2V | 13.5 ~ 16.5V   | 21.6 ~ 26.4V | 32.4 ~ 39.6V | 43.2 ~ 52.8V |
|                                         | VOLTAGE TOLERANCE <small>Note.3</small>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | ±3.0%                                                                                                                   | ±2.0%       | ±2.0%        | ±2.0%          | ±1.0%        | ±1.0%        | ±1.0%        |
|                                         | LINE REGULATION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | ±0.5%                                                                                                                   | ±0.5%       | ±0.5%        | ±0.5%          | ±0.5%        | ±0.5%        | ±0.5%        |
|                                         | LOAD REGULATION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | ±2.0%                                                                                                                   | ±1.5%       | ±1.0%        | ±1.0%          | ±1.0%        | ±1.0%        | ±1.0%        |
|                                         | SETUP, RISE TIME                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 2500ms, 50ms/230VAC      2500ms, 50ms/115VAC at full load                                                               |             |              |                |              |              |              |
| HOLD UP TIME (Typ.)                     | 20ms/230VAC      20ms/115VAC at full load                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                                                         |             |              |                |              |              |              |
| INPUT                                   | VOLTAGE RANGE <small>Note.6</small>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 90 ~ 264VAC      127 ~ 370VDC                                                                                           |             |              |                |              |              |              |
|                                         | FREQUENCY RANGE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 47 ~ 63Hz                                                                                                               |             |              |                |              |              |              |
|                                         | POWER FACTOR (Typ.) <small>Note.5</small>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | PF>0.95/230VAC      PF>0.98/115VAC at full load                                                                         |             |              |                |              |              |              |
|                                         | EFFICIENCY (Typ.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 80%                                                                                                                     | 82%         | 89%          | 90%            | 90%          | 90%          | 90%          |
|                                         | AC CURRENT (Typ.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 1.8A/115VAC      1 A/230VAC                                                                                             |             |              |                |              |              |              |
|                                         | INRUSH CURRENT (Typ.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | COLD START 60A/230VAC                                                                                                   |             |              |                |              |              |              |
| LEAKAGE CURRENT                         | <1mA/240VAC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                                                                                                         |             |              |                |              |              |              |
| PROTECTION                              | OVER LOAD                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 105 ~ 150% rated output power<br>Protection type : Hiccup mode, recovers automatically after fault condition is removed |             |              |                |              |              |              |
|                                         | OVER VOLTAGE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 3.7 ~ 4.45V                                                                                                             | 5.6 ~ 6.75V | 13.8 ~ 16.2V | 17.25 ~ 20.25V | 27.6 ~ 32.4V | 39.7 ~ 46.8V | 53.3 ~ 64.8V |
|                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Protection type : Shut down o/p voltage, re-power on to recover                                                         |             |              |                |              |              |              |
| ENVIRONMENT                             | WORKING TEMP.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | -30 ~ +70℃ (Refer to output load derating curve)                                                                        |             |              |                |              |              |              |
|                                         | WORKING HUMIDITY                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 20 ~ 90% RH non-condensing                                                                                              |             |              |                |              |              |              |
|                                         | STORAGE TEMP., HUMIDITY                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | -40 ~ +85℃, 10 ~ 95% RH                                                                                                 |             |              |                |              |              |              |
|                                         | TEMP. COEFFICIENT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | ±0.03%/℃ (0 ~ 50℃)                                                                                                      |             |              |                |              |              |              |
|                                         | VIBRATION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 10 ~ 500Hz, 2G 10min./1cycle, period for 60min. each along X, Y, Z axes                                                 |             |              |                |              |              |              |
| SAFETY & EMC<br><small>(Note 4)</small> | SAFETY STANDARDS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | UL60950-1, TUV EN60950-1 approved                                                                                       |             |              |                |              |              |              |
|                                         | WITHSTAND VOLTAGE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | I/P-O/P:3KVAC    I/P-FG:1.5KVAC    O/P-FG:0.5KVAC                                                                       |             |              |                |              |              |              |
|                                         | ISOLATION RESISTANCE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | I/P-O/P, I/P-FG, O/P-FG:100M Ohms / 500VDC/ 500VDC / 25℃ / 70% RH                                                       |             |              |                |              |              |              |
|                                         | EMI CONDUCTION & RADIATION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Compliance to EN55022 (CISPR22) Class B                                                                                 |             |              |                |              |              |              |
|                                         | HARMONIC CURRENT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Compliance to EN61000-3-2,-3                                                                                            |             |              |                |              |              |              |
| OTHERS                                  | EMS IMMUNITY                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Compliance to EN61000-4-2,3,4,5,6,8,11; ENV50204, EN55024, heavy industry level, criteria A                             |             |              |                |              |              |              |
|                                         | MTBF                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 345.3Khrs min.    MIL-HDBK-217F (25℃)                                                                                   |             |              |                |              |              |              |
|                                         | DIMENSION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | PCB:175*60*27mm (L*W*H) with optional CASE:195*68.5*33mm (L*W*H)                                                        |             |              |                |              |              |              |
|                                         | PACKING                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | PCB:0.25Kg; 48pcs/13Kg/0.85CUFT with optional CASE:0.54Kg; 25pcs/14.5Kg/0.59CUFT                                        |             |              |                |              |              |              |
| NOTE                                    | 1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25℃ of ambient temperature.<br>2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor.<br>3. Tolerance : includes set up tolerance, line regulation and load regulation.<br>4. The power supply is considered a component which will be installed into a final equipment. The final equipment must be re-confirmed that it still meets EMC directives.<br>5. 3.3V PF>0.92/230VAC, others PF>0.95/230VAC.<br>6. Derating may be needed under low input voltage. Please check the derating curve for more details. |                                                                                                                         |             |              |                |              |              |              |

## ■ Mechanical Specification



Unit:mm


Optional cover:  
No. 996A-T

AC Input Connector (CN1) : JST B3P-VH or equivalent


| Pin No. | Assignment | Mating Housing           | Terminal                          |
|---------|------------|--------------------------|-----------------------------------|
| 1       | AC/L       | JST VHR<br>or equivalent | JST SVH-21T-P1.1<br>or equivalent |
| 2       | No Pin     |                          |                                   |
| 3       | AC/N       |                          |                                   |

DC Output Connector (CN2) : JST B6P-VH or equivalent


| Pin No. | Assignment | Mating Housing           | Terminal                          |
|---------|------------|--------------------------|-----------------------------------|
| 1,2,3   | -V         | JST VHR<br>or equivalent | JST SVH-21T-P1.1<br>or equivalent |
| 4,5,6   | +V         |                          |                                   |



### ■ Block Diagram



### ■ Output Derating



### ■ Output Derating VS Input Voltage

